

planika  
INTELLIGENT FIRE

# GAS FIREPLACES

indoor and outdoor



2018

# VALENTINO

## FEATURES:

- Linear-shape burner
- Anti-reflective glass
- LPG / Natural Gas powered
- CO sensor
- Gas sensor
- Seismic activity sensor
- Child lock
- Advanced thermostat
- Service reminder
- Remote control
- Smart Home System compatible
- Wi-Fi (mobile device control)
- 15 levels of flame height
- Eco flow mode
- Modular burner
- Natural-looking accessories
- Heat inflector

## TECHNICAL DATA:

Front glass length [mm]	1000		1300	
Fuel option	Natural gas (G20/G25)	LPG (G30/G31)	Natural gas (G20/G25)	LPG (G30/G31)
Nominal Heat Output [kW]	6,4	6,7	8,5	7,4
Nominal Heat Input (Hi) [kW]	8,5	8,9	11,3	9,9
Gas consumption [m³/h]	0,25-0,9	-	0,29-1,2	-
Gas consumption [kg/h]	-	0,2-0,7	-	0,2-0,78
Interior	Matt black painted steel / optional rear lining: black ceramic glass (high gloss)		Matt black painted steel / optional rear lining: black ceramic glass (high gloss)	
Flue system [mm]	Concentric flue 200/130		Concentric flue 200/130	

## FRONT FACING



Valentino 1000 F  
Valentino 1300 F

## DOUBLE SIDED (CORNER)



Valentino 1000 LF / FR  
Valentino 1300 LF / FR

## THREE SIDED



Valentino 1300 LFR

# MONROE

## FEATURES:

- Campfire burner
- Anti-reflective glass
- LPG / Natural Gas powered
- CO sensor
- Gas sensor
- Seismic activity sensor
- Child lock
- Advanced thermostat
- Service reminder
- Remote control
- Smart Home System compatible
- Wi-Fi (mobile device control)
- 15 levels of flame height
- Eco flow mode
- Modular burner
- Natural-looking accessories
- Heat inflector

## TECHNICAL DATA:

Front glass length [mm]	900	
Fuel option	Natural gas (G20/G25)	LPG (G30/G31)
Nominal Heat Output [kW]	8,3	9,2
Nominal Heat Input (Hi) [kW]	11,0	12,2
Gas consumption [m <sup>3</sup> /h]	0,22-1,2	-
Gas consumption [kg/h]	-	0,20-0,96
Interior	Matt black painted steel / optional rear lining: black ceramic glass (high gloss) or brick panel	Matt black painted steel / optional rear lining: black ceramic glass (high gloss) or brick panel
Flue system [mm]	Concentric flue 200/130	Concentric flue 200/130

## FRONT FACING



Monroe 900 F



## DOUBLE SIDED (CORNER)



Monroe 900 LF / FR



## THREE SIDED



Monroe 900 LFR



# VERSAL

## FEATURES:

- 15 levels of flame height
- LPG or Natural Gas powered
- Convectional fan
- Ambient lighting
- Easy installation to existing chimneys
- Child lock
- Eco flow mode
- Remote control
- Smart Home System compatible
- Automatic ignition
- CE Certified
- Ceramic glass

## TECHNICAL DATA:

Length [mm]	400		600		750		900	
Fuel option	NG (G20/G25)	LPG (G30/G31)	NG (G20/G25)	LPG (G30/G31)	NG (G20/G25)	LPG (G30/G31)	NG (G20/G25)	LPG (G30/G31)
Nominal Heat Input [Hi] [kW]	3,0	3,8	4,6	4,9	5,3	6,0	7,5	7,6
Gas consumption [m <sup>3</sup> /h]	max. 0,32	-	max. 0,49	-	max. 0,56	-	max. 0,79	-
Gas consumption [kg/h]	-	max. 0,3	-	max. 0,39	-	max. 0,47	-	max. 0,6
Interior	Matt black painted steel / optional lining: black ceramic glass (high gloss) or brick panel		Matt black painted steel / optional lining: black ceramic glass (high gloss) or brick panel		Matt black painted steel / optional lining: black ceramic glass (high gloss) or brick panel		Matt black painted steel / optional lining: black ceramic glass (high gloss) or brick panel	
Flue system	Convectional flue		Convectional flue		Convectional flue		Convectional flue	

## VERSAL INSERT



Versal Insert 400



Versal Insert 600



Versal Insert 750



Versal Insert 900

## VERSAL FREESTANDING



Versal Freestanding 400



Versal Freestanding 600



Versal Freestanding 750



Versal Freestanding 900

## VERSAL FREESTANDING WITH WOODBOX



Versal Woodbox 400



Versal Woodbox 600



Versal Woodbox 750



Versal Woodbox 900



# SINATRA

## FEATURES:

- Linear-shape burner
- 15 levels of flame height
- LPG or Natural Gas powered
- Safety sensors
- Child lock
- Eco flow mode
- Module division mode
- Remote control
- Smart Home System compatible
- Automatic ignition
- CE Certified
- Ceramic glass
- No glazing possible
- Bespoke sizes

## TECHNICAL DATA:

Front glass length [mm]	1200		1600		2000		2400	
Fuel option	NG (G20/G25)	LPG (G30/G31)	NG (G20/G25)	LPG (G30/G31)	NG (G20/G25)	LPG (G30/G31)	NG (G20/G25)	LPG (G30/G31)
Nominal Heat Input (Hi) [kW]	10,31	9,51	14,95	14,26	19,74	19,01	19,75	19,96
Gas consumption [m <sup>3</sup> /h ]	max. 1,09	-	max. 1,58	-	max. 2,09	-	max. 2,09	-
Gas consumption [kg/h]	-	max. 0,75	-	max. 1,12	-	max. 1,50	-	max. 1,57
Interior	Matt black painted steel / optional rear lining: black ceramic glass (high gloss)		Matt black painted steel / optional rear lining: black ceramic glass (high gloss)		Matt black painted steel / optional rear lining: black ceramic glass (high gloss)		Matt black painted steel / optional rear lining: black ceramic glass (high gloss)	
Flue system	Conventional flue		Conventional flue		Conventional flue		Conventional flue	

## FRONT FACING



Sinatra 1600 F  
Sinatra 2000 F  
Sinatra 2400 F

## DOUBLE SIDED (CORNER)



Sinatra 1600 LF / FR  
Sinatra 2000 LF / FR  
Sinatra 2400 LF / FR

## THREE SIDED



Sinatra 1600 LFR  
Sinatra 2000 LFR  
Sinatra 2400 LFR

## TUNNEL



Sinatra 1200 TU  
Sinatra 1600 TU  
Sinatra 2000 TU  
Sinatra 2400 TU

## ROOM DIVIDER



Sinatra 1200 RD  
Sinatra 1600 RD  
Sinatra 2000 RD  
Sinatra 2400 RD

## ISLAND



Sinatra 1200 IS  
Sinatra 1600 IS  
Sinatra 2000 IS  
Sinatra 2400 IS

# GALIO

## FEATURES:

- For outdoor use
- Easy installation
- Flame height regulation
- Linear-shape burner
- LPG/NG powered
- No electrical connection required
- CE certified components
- Bespoke sizes
- Possibility of joining modules
- Easy start button
- SHS compatible
- Remotely controlled

## TECHNICAL DATA:

Fuel option	Galio Insert		Galio Corten	
	Natural gas (G20/G25)	LPG (G30/G31)	Natural gas (G20/G25)	LPG (G30/G31)
Heat Output [kW]	4,7 - 9,4	6,3 - 11,8	4,7 - 9,4	6,3 - 11,8
Gas consumption [m³/h]	0,5-1	-	0,5-1	-
Gas consumption [kg/h]	-	0,5-0,93	-	0,5-0,93
Gas pressure [mbar]	20	37	20	37
Interior	stainless steel		CASING: corten steel + tempered glass BURNER: stainless steel	
Dimensions	1027 mm x 230 mm x 260 mm		1140 mm x 350 mm x 500 mm	

## GALIO INSERT



## GALIO CORTEN



## ACCESSORIES



Corten case  
(Accessory for Galio Corten gas bottle)



Galio cover

# GALIO FIRE PIT

## FEATURES:

- For outdoor use
- Easy installation
- Flame height regulation
- Round-shape burner
- LPG/NG powered
- Safety sensor
- No electrical connection required
- CE certified components
- Bespoke sizes
- Easy start button
- SHS compatible
- Remotely controlled

## TECHNICAL DATA:

Fuel option	Galio Fire Pit Insert		Galio Fire Pit Corten	
	Natural gas (G20/G25)	LPG (G30/G31)	Natural gas (G20/G25)	LPG (G30/G31)
Heat Output [kW]	2,4 - 4,7	2,5 - 5,1	2,4 - 4,7	2,5 - 5,1
Gas consumption [m³/h]	0,25-0,5	-	0,25-0,5	-
Gas consumption [kg/h]	-	0,2-0,4	-	0,2-0,4
Gas pressure [mbar]	20	37	20	37
Interior	stainless steel		CASING: corten steel BURNER: stainless steel	
Dimensions	450 mm x 246 mm		950 mm x 350 mm	

## GALIO FIRE PIT INSERT



## GALIO FIRE PIT CORTEN



## ACCESSORIES



Corten case  
(Accessory for Galio Corten gas bottle)

# PRODUCT COMPARISON

ADDITIONAL OPTIONS AND FUNCTIONS

	VALENTINO	MONROE	VERSAL	SINATRA
FLUE SYSTEM	BALANCED 200/130	BALANCED 200/130	CONVENTIONAL	CONVENTIONAL
ANTI-REFLECTIVE GLAZING	STANDARD	STANDARD	-	OPTIONAL
NO GLASS ENCLOSURE	-	-	-	OPTIONAL
BLACK CERAMIC GLASS (REAR LINING)	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
BRICK PANEL (REAR LINING)	-	OPTIONAL	OPTIONAL	OPTIONAL
LED LIGHTING + CRYSTAL DIAMOND EMBERS	-	-	-	OPTIONAL
AMBIENT LIGHTING	-	-	STANDARD	-
CERAMIC LOGS + VERMICULITE	STANDARD	STANDARD	STANDARD	OPTIONAL
BLACK DIAMOND STONES	STANDARD	-	-	STANDARD
WHITE PEBBLES	STANDARD	-	-	STANDARD
BLACK GLASS EMBERS	-	-	-	STANDARD
CHILD LOCK	STANDARD	STANDARD	STANDARD	STANDARD
ECO FLOW MODE	STANDARD	STANDARD	STANDARD	STANDARD
THERMOSTAT	STANDARD	STANDARD	-	-
SMART HOME SYSTEM COMPATIBILITY	STANDARD	STANDARD	STANDARD	STANDARD
REMOTE CONTROL	STANDARD	STANDARD	STANDARD	STANDARD
WI-FI AND SERVICE REMINDER	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
CO SENSOR	STANDARD	STANDARD	-	STANDARD
GAS SENSOR	STANDARD	STANDARD	-	STANDARD
SEISMIC ACTIVITY SENSOR	STANDARD	STANDARD	STANDARD	STANDARD
BURNER	1 CENTRAL & 2 SIDE BURNERS	1 UPPER & 1 LOWER	1	MULTIPLE, DEPENDING ON LENGTH
WALL BRACKET	-	-	OPTIONAL	-
WOODBBOX	-	-	OPTIONAL	-
HEAT INFLECTOR	STANDARD	STANDARD	-	-
CUSTOMIZATION	-	-	AVAILABLE	AVAILABLE
CONVECTIONAL FAN	-	-	STANDARD	-